N	описание	схема	размери см L	размери см H	кота +0.00 брой	площ кв.м
П1	дограма алуминиева, петкамерна, бяла, скосен фалц, с тройно уплътнение между крило и каса - EPDM, с Air controller - за автоматично проветряване стъклопакет двоен, въздушна междина >10мм, външно нискоемисионно стъкло 4мм, вътрешно обикновено 4мм, U-стойност: <1 W/(m2K) g-стойност: 45 % обков тристранно регулируем, с държач, базисна степен на сигурност, секюрити дръжки отваряема: на хоризонтална ос		100	57	9	5,13
П2	дограма алуминиева, петкамерна, бяла, скосен фалц, с тройно уплътнение между крило и каса - EPDM, с Air controller - за автоматично проветряване стъклопакет двоен, въздушна междина >10мм, външно нискоемисионно стъкло 4мм, вътрешно обикновено 4мм, U-стойност: <1 W/(m2K) g-стойност: 45 % обков тристранно регулируем, с държач, базисна степен на сигурност, секюрити дръжки отваряема: на хоризонтална ос		130	45	18	10,53
П3	дограма алуминиева, петкамерна, бяла, скосен фалц, с тройно уплътнение между крило и каса - EPDM, с Air controller - за автоматично проветряване стъклопакет двоен, въздушна междина >10мм, външно нискоемисионно стъкло 4мм, вътрешно обикновено 4мм, U-стойност: <1 W/(m2K) g-стойност: 45 % обков тристранно регулируем, с държач, базисна степен на сигурност, секюрити дръжки отваряема: на вертикална ос		180	110	20	39,60
П4	дограма алуминиева, петкамерна, бяла, скосен фалц, с тройно уплътнение между крило и каса - EPDM, с Air controller - за автоматично проветряване стъклопакет двоен, въздушна междина >10мм, външно нискоемисионно стъкло 4мм, вътрешно обикновено 4мм, U-стойност: <1 W/(m2K) g-стойност: 45 % обков тристранно регулируем, с държач, базисна степен на сигурност, секюрити дръжки отваряема: на вертикална ос		180	130	8	18,72

ВЪЗЛОЖИТЕЛ

ОБЩИНА БОТЕВГРАД, КМЕТ - ИВАН ГАВАЛЮГОВ

проектната документация представлява инвестиционен проект по смисъла на ЗУТ,
за обществена сграда, 3-та категория, съгласно чл.137, ал. 1, т.3, буква "в" от ЗУТ,
разработена от правоспособни проектанти при спазване на нормативната база в Република България.

Архитектурното заснемане на спортна зала "Балкан" - Ботевград
е част от документацията на проекта "Инвестираме в спорта за кариерно развитие на млади хора - двигател на интелигентен растеж и сближаване на общините Ботевград /BG/ и Лесковац /RS/"
по програма Интеррег-ИПП за трансгранично сътрудничество България-Сърбия, 2014TC16 I 5CB007,
покана за подаване напредложения №2014TC16 I 5CB007 - 2015 - 1, Приоритетна ос 2: "Младежи",
Специфична цел 2.1. "Умения и предприемачество"

Дограма се изпълнява по спесификация към проектната документация след вземане на мерки от място
Всички мерки за врати се вземат от готов под,завършени работи по стени и положена подова настилка
Цветовата гама и декорът на покритието се избират заедно от възложител, проектант и изпълнител.

ИЗПЪЛНИТЕЛ

АНДРЮ_05 ЕООД
управление на проекти & комплексно проектиране
[] тел: 0723/66248 [] fax: 66 249 [] e-mail: mariellaandreevska@yahoo.com []

ОБЕКТ

СПОРТНА ЗАЛА "БАЛКАН"
В УПИ I ПО ПР И ПИ 05815.301.396 ПО КК И КР
БОТЕВГРАД, ОБЩИНА БОТЕВГРАД, ОБЛАСТ СОФИЙСКА

фаза: ТП
ЯНУАРИ 2016

СПЕСИФИКАЦИЯ ПРОЗОРЦИ

архитектура	арх.МариелаАндреевска	част: АРХ
	арх.Елена Николова	М 1: 50
ръководител проект	арх.МариелаАндреевска	лист № 1/4

УПРАВИТЕЛ

ЗА "АНДРЮ_05" ЕООД
.....
/арх. Мариела Андреевска/

ГЛАВЕН АРХИТЕКТ:

този проект е защитен от закона за авторското право
и може да се ползва само с изричното съгласие на
"АНДРЮ_05" ЕООД
и съгласно договореностите между участниците в инв. процес
Логото на "АНДРЮ_05" ЕООД
да се вижда на която и да е репродукция,
копие и свързаните с ползването електронни документи.

Technical specifications – windows

W 1 – 5-chamber white aluminum joinery, rabbeted bevel, triple gasket between casement seal and wing – EPDM, with Air controller – for automatic ventilation; double glazing packer; air intermediate > 10 mm, outward low-emission glass 4 mm, inward glass – 4 mm, U value < 1 W (m2K) g- value 45 %, 3 – side adjustable casing, with basic safety extent, security handles

Open able: horizontal sliding

W 2 - 5-chamber white aluminum joinery, rabbeted bevel, triple gasket between casement seal and wing – EPDM, with Air controller – for automatic ventilation; double glazing packer; air intermediate > 10 mm, outward low-emission glass 4 mm, inward glass – 4 mm, U value < 1 W (m2K) g- value 45 %, 3 – side adjustable casing, with basic safety extent, security handles

Open able: horizontal sliding

W 3 - 5-chamber white aluminum joinery, rabbeted bevel, triple gasket between casement seal and wing – EPDM, with Air controller – for automatic ventilation; double glazing packer; air intermediate > 10 mm, outward low-emission glass 4 mm, inward glass – 4 mm, U value < 1 W (m2K) g- value 45 %, 3 – side adjustable casing, with basic safety extent, security handles

Open able: vertical sliding

W 4 - 5-chamber white aluminum joinery, rabbeted bevel, triple gasket between casement seal and wing – EPDM, with Air controller – for automatic ventilation; double glazing packer; air intermediate > 10 mm, outward low-emission glass 4 mm, inward glass – 4 mm, U value < 1 W (m2K) g- value 45 %, 3 – side adjustable casing, with basic safety extent, security handles

Open able: vertical sliding

Construction project drawings and specifications represents investment project as indicated in the Law of spatial planning for a building for public servicing, - third category in according to arc. 137, para 1, item 3, l. “v” from Law of spatial planning. The project drawings and specifications are developed from licensed project designers with regard to the regulatory base of Republic of Bulgaria.

The present situation drawing of the sports hall “Georgi Hristov”/ “Balkan”, Botevgrad is part of the construction project drawings and specifications of the project “We invest in sport for career development of young people – the motive power of smart growth and cohesion between the Municipalities of Botevgrad and Leskovac” under Interreg-IPA Cross-border Cooperation Bulgaria-Serbia Programme, 2014TC16I5CB007, call for project proposals № 2014TC16I5CB007-2015-1, Priority Axis 2: “Youths”, Specific objective 2.1: “Skills & Entrepreneurship”

The mount of joinery shall be made in accordance to the technical specifications, part of the construction project drawings and specifications, and after taking measures at place. All measures for doors shall include floor, finished works on walls and flooring. The range of colors and the décor on the coverage will be chosen from the Contracting Authority, project designer and Contractor.

<table>
<tr><td>DESIGNER</td><td colspan="3">ANDRIY_05 EOOD
Project management and designing
Tel. 0723/66248 Fax. 66249,
email:mariellaandreevska@yahoo.com</td></tr>
<tr><td rowspan="2"></td><td colspan="2">Sorts Hall “Balkan”
Regulated Surveyed Land Plot I under the Regulation Plan and Land Plot 05815.301.396 under Cadastral Map and Cadastral Registry</td><td>Phase: TP
January 2016</td></tr>
<tr><td colspan="4">Specification windows</td></tr>
<tr><td rowspan="3">Design team</td><td>Architecture</td><td>Arch. Mariela Andreevska</td><td>Part Arch.</td></tr>
<tr><td></td><td>Arch Elena Nikolova</td><td>M 1:50</td></tr>
<tr><td>Project manager</td><td>Arch. Mariela Andreevska</td><td>Page 1/4</td></tr>
</table>